



Cameo Platinum Diamond Grinding Discs





Cameo Platinum Diamond Grinding Discs





Cameo Platinum Surface detail

Diamond abrasive in Cameo surface 3D

Cameo Platinum P80 - P100 and Cameo Platinum P120 - P150 are to be used for their high stock removal capacity on rather hard materials and for the preparation of large samples.

Cameo Platinum P220 - P320, Cameo Platinum P400 - P600 and Cameo Platinum P1000 - P1200 will guarantee a better finish on smaller hard samples and on softer ferrous or non ferrous samples.

Water is employed as a lubricant in general but for samples susceptible to attack by water an oil can be used.

Recommended rotation speed for the Cameo Platinum discs is 150 rpm. Increasing the speed can increase the stock removal but it can increase the need for more regular dressing.

The Cameo Platinum disc is supplied with a protective film on its surface and thus needs dressing prior to use with the included dressing stick. To ensure consistent and effective operation regular dressing is required.

Dressing periods will vary dependent on the amount, size & hardness of the specimen. Please contact your local Area Sales Manager if you require any particular assistance on this.

To dress the Cameo Platinum disc first place the disc on the platen and rotate it a 150 rpm with copious water applied. Using moderate pressure apply the correct dressing stick manually to the centre of the disc and move it slowly to the edge.

MetPrep Technical Bulletin 0008 - 2015. For further information please contact sales@metprep.co.uk

MetPrep Ltd - Curriers Close, Charter Avenue, Coventry, CV4 8AW - 02476 421222