

GRINDING & POLISHING MACHINE

QPOL 300 M2



The Qpol 300 M2 is a manual, twin wheel grinding and polishing machine for **separately controlled working wheels Ø 250/300 mm**.

In the ergonomically integrated **touch panel**, all process parameters as well as convenient features for manual preparation are clearly displayed and can be easily changed at any time. All process parameters can be saved as a preparation method. The **adjustable timer** and the torque display for **visualizing the current grinding pressure** enable comfortable and **reproducible** manual **preparation steps**. The water valve is automatically switched on/off when the preparation starts or ends.

A spin cycle function (**Cleaning Boost**) helps to spin dry the grinding and polishing medium at 750 rpm at the end of the preparation process within 3 seconds and then turns off the device. The particularly strong, speed-controlled drive makes this model suitable for all preparation steps and materials. In addition, the working disc can be operated in **clockwise / counter-clockwise** rotation.

The impact-resistant plastic bowl, the **powder-coated aluminium housing** and the high-quality components inside the device are the basis for smooth running and best preparation results. The robust device can be retrofitted with the Qpol Go automatic grinding and polishing head and combined with the Qdoser GO and Qdoser ONE manual dosing system. It therefore offers a high degree of **flexibility** and **comfort** during sample preparation.

PRODUCT ADVANTAGES

- | Double wheel grinder/polisher for metallographic sample preparation
- | Variable speed
- | Visualization of the current grinding force
- | Timer function
- | Automatic water valve
- | Aluminium case, powder coated
- | Clockwise and counter-clockwise rotation
- | Easy cleaning/rinsing of bowl by lifting the working wheel (single-disc design)
- | Impact-proof plastic bowl
- | Retrofittable automatic grinding/polishing head Qpol GO



GRINDING & POLISHING MACHINE QPOL 300 M2

TECHNICAL DATA

Working wheels	Ø 250/300 mm
Speed	30 - 600 rpm, continuously adjustable
Connection power	2.3 kVA
Drive power (main drive)	2x 0.75 kW (S1)
W x H x D	901 x 265 x 710 mm
Weight	~ 57 - 65 kg
Water connection	1x fresh water connection R½" max. 6 bars
Dosing system (option)	Qdoser GO or Qdoser ONE
Polishing head (retrofitable option)	Qpol GO

QDOSER GO

The automatic dosing system QDOSER GO is universally suitable for use with all manual grinders. Four 500 ml glass bottles with screw caps hold 3 x suspension and 1 x lubricant or 4 x Dia-Complete and can be filled via a separate lid. They are easily removed for cleaning.

The holder for dosing nozzles for manual dosage may be freely positioned on the machine. The dosage interval can be variably set via the control panel. The backflushing function keeps the hoses clean.



- | Automatic dosing unit for
3x diamond suspension and 1x lubricant or
4x Dia-Complete
- | Dosing interval adjustable
- | Reverse rinsing function
- | Manual or automatic mode
- | For all grinders and polishers
- | Suspension containers refillable and removable

www.qatm.com/qpol300m2